# Технические характеристики

#### По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46

Россия (495)268-04-70

Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Липецк (4742)52-20-81 Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Нижний Новгород (831)429-08-12

Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Симферополь (3652)67-13-56

[азахстан (7172)727-132

Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-93



## FORM HOOK WITH G10 PIN

**ACCESSORIES - HOOKS** 

Blue painted open mould hook without lock in strength class G10. Suitable for use where the opening of other hooks is not sufficient - especially in foundry applications.

Carrying capacity: 2,5 t, 4 t, 6,7 t



#### **FORM HOOK WITH G8 PIN**

ACCESSORIES - HOOKS

Red painted open mould hook without lock in strength class G8. Suitable for use where the opening of other hooks is not sufficient - especially in foundry applications. This is why the mould hook is often also called a foundry hook.

Carrying capacity: 2 t, 3,15 t, 5,3 t



## FORM HOOK WITH G10 EYE

ACCESSORIES - HOOKS

Blue painted open mould hook without lock in strength class G10. Suitable for use where the opening of other hooks is not sufficient - especially in foundry applications.

Carrying capacity: 1,4 t, 2,5 t, 4 t, 6,7 t, 10 t



# **COOKING HOOK**

**ACCESSORIES - HOOKS** 

The welding hook can be used for welding on crane traverses, excavators, loaders, etc. It can also be used for welding on excavator shovels, tractor excavators. The hook is welded in normal conditions, no preheating is required. Includes a safety lock for maximum safety.

Carrying capacity: 1 t, 2 t, 3 t, 5 t, 8 t



#### FORM HOOK WITH G8 EYE

ACCESSORIES - HOOKS

Red painted open mould hook without lock in strength class G8. Suitable for use where the opening of other hooks is not sufficient - especially in foundry applications.

Carrying capacity: 1,12 t, 1,6 t, 2 t, 3,15 t, 5,3 t



## **SWIVEL COUPLING SP**

**ACCESSORIES - CONNECTING LINKS** 

SP swivel coupling for rope and chain ties. The swivel clutch prevents twisting of the rope or other work tools. It is manufactured in strength class G80. It allows 360° rotation and thus eliminates any twisting.

Carrying capacity: 2 t, 3,15 t, 5,3 t



#### **DIPPING D - EYE**

ACCESSORIES - EYE

D-shaped binding lugs are designed for welding, for example, on automotive structures or machine parts. They are used to attach loads to the binding means. The welding eye contains an integrated spring which causes the eye to remain in the desired position. It is therefore permanently fixed and does not move. The range of movement of the eye is 180°. The welding surface contains protrusions that create space for the weld. The eye is designed for welding on a flat surface.

Carrying capacity: 1,2 t, 2 t, 3,15 t, 5,3 t



## **HOOK WITH EYE AND LOCK G8**

**ACCESSORIES - HOOKS** 

The most common red painted hook with eye and galvanized lock. Red lacquered hook with eye and galvanized lock in strength class G8.

Load: 1,2 t, 2 t, 3,15 t, 5,3 t, 8 t



## **HOOK WITH G8 FORK**

ACCESSORIES - HOOKS

The hook with connecting pin and lock in strength class G8 is attached directly to the chain, no coupling is required. The hook includes a safety lock and is suitable for general use.

For chain /load capacity: 6 mm / 1.12t, 7/8 mm / 2t, 10 mm / 3.15t, 13 mm / 5.3t



#### HANGING EYE A

ACCESSORIES - EYE

Hanging eye for wire rope and chain ties made of steel class 8.

Carrying capacity: 5,3 t, 8 t, 1,6 t, 2,12 t, 3,15 t



## SHORTENING HOOK WITH G8 FORK

ACCESSORIES - HOOKS

The shortening hook with fork is used to shorten the chain. A parallel hook with a connecting pin (often referred to as a shortener) in strength class G8 is used to shorten the chain. Suitable when handling uneven loads or loads that are not balanced and one or more strands need to be shortened. It can also be used to shorten all strands and adjust the entire chain to suit the needs.

Into the chain: 6 mm, 7/8 mm, 10 mm, 13 mm



#### **CONNECTING LINK WG**

ACCESSORIES - CONNECTING LINKS

It is used as an intermediate link, transition link and return link. The WG (Connex) link in strength class G8 is used as an intermediate link, transition link and return link. It can also be used as a small suspension link and a small end link.

For chain: 6 mm, 7/8 mm, 10 mm, 13 mm



## **SWIVEL HOOK**

**ACCESSORIES - HOOKS** 

Swivel hook with safety catch. Red lacquered swivel hook with galvanised safety catch.

Carrying capacity: 0,75 t, 1 t, 1,5 t, 2 t, 3 t, 4,5 t



#### **TOWING HOOK FOR WINCHES**

ACCESSORIES - HOOKS

Towing hook for winches (grappling hook, with lock), finish: zinc plated.

Carrying capacity: 500 kg, 1000 kg



## SIKA HOOK

**ACCESSORIES - HOOKS** 

Hook SIKA green lacquered. Carrying capacity: 0,5 t, 1 t



#### **HOOK WITH EYE DIN 689**

ACCESSORIES - HOOKS

Hook with eye DIN 689 (hook, with safety catch). Carrying capacity: 250 kg, 500 kg, 1000 kg



## **CONNECTING LINK - OMEGA G80**

**ACCESSORIES - CONNECTING LINKS** 

The Omega-shaped link is suitable for all G80 high-strength chains. It is suitable for connecting the chain and the selected component - especially the lugs.

Chain diameter / load capacity: 6 mm / 1.12 t, 8 mm / 2 t, 10 mm / 3.15 t, 13 mm / 5.3 t, 16 mm / 8 t



## **HOOK WITH EYE**

ACCESSORIES - HOOKS

Red lacquered hook with eye and metal lock. Carrying capacity: 0,75 t, 1 t, 1,5 t, 2 t, 3 t, 4,5 t



## **SLIDING HOOK WITH FORK**

**ACCESSORIES - HOOKS** 

Sliding hook with fork 331C is made of hardened steel C45E, surface finish: yellow galvanized zinc.

Carrying capacity: 1,25 t, 1,95 t, 2,38 t, 3,18 t



## **CARABINER HOOK**

ACCESSORIES - HOOKS

Carabiner hook (with large eye, with safety catch) is made of forged steel C15, load capacity 500kg, surface finish: galvanized.

55737



#### S - HOOK

ACCESSORIES - HOOKS

The S-hook is a special type of hook that finds use in specific manipulations where standard hook types are not suitable. The S-hook has an open design.

Log diameter / load capacity: 12 mm/ 0.3 t, 16 mm/ 0,5 t, 20 mm/ 1 t, 22 mm/ 1.25 t



#### SHORTENING HOOK WITH FORK

ACCESSORIES - HOOKS

Shortening hook with fork 330C is made of hardened steel C45E, finished in yellow galvanised zinc.

Carrying capacity: 1,17 t, 1,76 t, 2,43 t, 3,24 t



#### **TOWING HOOK**

**ACCESSORIES - HOOKS** 

The towing hook (tie hook, with safety catch) is made of forged steel C15, load capacity 3500kg, surface finish: zinc.

52070



#### TOWING HOOK WITH WELDED TRIANGLE

**ACCESSORIES - HOOKS** 

Towing hook with welded triangle, capacity 780 kg, galvanized.

55669



## **NUT WITH G8 EYE**

ACCESSORIES - EYE

High-strength hanging nut with eye in strength class G8. The surface is completely painted red.

Thread: M 6, M 8, M 10, M 12, M 16, M 20, M 24



#### TYPE U HA1 HIGH-STRENGTH PULLEY

ACCESSORIES - CALIPERS

High-strength U-beam - straight. The strap is used for connecting various components with a rope or chain and is used especially during frequent disassembly. When assembling, it is necessary to tighten the bolt sufficiently to prevent the locking bolt from loosening due to shocks.

Carrying capacity: 0,75 t, 1 t, 1,5 t, 2 t, 3,25 t, 4,75 t, 6,5 t, 8,5 t, 9,5 t



# **EYE BOLT G8**

ACCESSORIES - EYE

High-strength hinge bolt with eye in strength class G8. The surface is completely painted red.

Thread: M 6, M 8, M 10, M 12, M 16, M 20, M 24



## AGRICULTURAL HOOK

ACCESSORIES - HOOKS

Agricultural hook (tying hook) in surface finish: galvanized.

Carrying capacity: 300 kg, 600 kg



## **TYPE HA2 HIGH-STRENGTH STRAP**

**ACCESSORIES - CALIPERS** 

High-strength type  $\Omega$  - arched. The belt is used for connecting various components with rope or chain, it is used especially for frequent disassembly, which is quick and easy thanks to its design.

Carrying capacity: 0,5 t, 0,75 t, 1 t, 1,5 t, 2 t, 3,25 t, 4,75 t, 6,5 t, 8,5 t, 9,5 t



#### **SELF-LOCKING CAST BUCKLE**

ACCESSORIES - READ MORE

Self-locking buckle (buckle) for clamping belts.

Strap width: 25 mm, 35 mm, 50 mm



## **SCREW WITH EYE ACCORDING TO DIN 580**

**ACCESSORIES - EYE** 

Eye bolt to DIN 580, galvanized, metric standard thread.

Thread: M 6, M 8, M 10, M 12, M 14, M 16, M 18, M 20, M 22, M 24, M 27, M 30, M 36



#### **NUT WITH EYE ACCORDING TO DIN 582**

ACCESSORIES - EYE

Nut with eye according to DIN 582, galvanized, metric standard thread.

Thread: M 6, M 8, M 10, M 12, M 14, M 16, M 18, M 20, M 22, M 24, M 27, M 30, M 36



#### **FLAT ROPE CLAMP**

ACCESSORIES - CLAMPS, EYELETS

Flat wire rope clamp (oval clamp), cast iron clamp for fixed connections of steel wire ropes with a diameter of 2 - 6mm suitable where the shape of conventional clamps can be an obstacle. There are 5 sizes available in the 2-6mm size range. Supplied with a white electroplated zinc finish.

Rope diameter: 2 mm, 3 mm, 4 mm, 5 mm, 6 mm



## FORGED STRAIGHT STIRRUP

**ACCESSORIES - CALIPERS** 

Straight, galvanized forged bar.

Size: 8 mm, 10 mm, 11 mm, 12 mm, 14 mm, 16 mm, 19 mm, 22 mm



## **OMEGA FORGED TRUNK**

**ACCESSORIES - CALIPERS** 

Wrought, omega type, galvanized.

Size: 8 mm, 10 mm, 11 mm, 12 mm, 14 mm, 16 mm, 19 mm, 22 mm



#### **ROPE CLAMP DIN 1142**

ACCESSORIES - CLAMPS, EYELETS

Rope clamp DIN 1142 (rope clamp), strength clamp with solid cast iron base and flanged nuts designed for connecting wire ropes and making rope lugs.

Rope diameter: 5 mm, 6,5 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 19 mm, 22 mm



## **ROPE CLAMP DUPLEX**

ACCESSORIES - CLAMPS, EYELETS

The duplex wire rope clamp is used to form the lugs on the wire rope. Not suitable for lifting!

Rope diameter: 2 mm, 3 mm, 4 mm, 5 mm, 6 mm, 8 mm



## **ROPE CLAMP DIN 741**

ACCESSORIES - CLAMPS, EYELETS

Rope clamp DIN 741 (rope clamp), a standard rope clamp designed for connecting wire ropes and making rope lugs. For stronger connections we offer strength rope clamps according to DIN 1142.

For rope diameter: 3 mm, 5 mm, 6,5 mm, 8 mm, 10/11 mm, 12/13 mm, 14 mm, 16 mm, 19 mm, 22 mm



# **ROPE EYELET, TYPE A**

ACCESSORIES - CLAMPS, EYELETS

Rope diameter: 2,5 mm, 3 mm, 4 mm, 5 mm, 6 mm, 7 mm, 8 mm, 10 mm, 11 mm, 12 mm, 14 mm, 16 mm, 18 mm, 20 mm



# **ROPE EYELET, TYPE B**

ACCESSORIES - CLAMPS, EYELETS

Rope diameter: 2,5 mm, 3,5 mm, 4 mm, 5 mm, 6 mm, 7 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, 20 mm



## **ROPE CLAMP SIMPLEX**

ACCESSORIES - CLAMPS, EYELETS

The simplex rope clamp is used to form the lugs on the wire rope. Not suitable for lifting!

Rope diameter: 2 mm, 3 mm, 4 mm, 5 mm, 6 mm, 8 mm



## **SWIVEL BINDING POINT**

ACCESSORIES - EYE

The binding point is terminated by an eye, which is placed in a rotating segment on ball bearings. This makes turning easy.

Thread / load capacity: M12 / 0.5t, M16 / 1.12 t, M20 / 2t, M24 / 3.15 t



#### HANGING EYE WITH FORK

ACCESSORIES - EYE

Hanging eye with fork for rope and chain slings.

Carrying capacity: 2 t, 3,15 t, 5,3 t



#### **ALUMINIUM SLEEVE**

ACCESSORIES - CLAMPS, EYELETS

The aluminium sleeve EN 13411-3 (DIN3093A) is used to form the lugs on the rope or to connect two ropes. In order for the formed joint to have the prescribed load capacity according to the standards, this sleeve must be pressed in presses and dies designed for pressing in high pressure presses.

Rope diameter: 1 mm, 1,6 mm, 2 mm, 2,5 mm, 3 mm, 4 mm, 5 mm, 6 mm, 7 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, 20 mm, 22 mm, 24 mm

#### По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89 Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Россия (495)268-04-70 Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12

Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Пермь (342)205-81-47 Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Симферополь (3652)67-13-56

Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Тверь (4822)63-31-35 Томск (3822)98-41-53 Тула (4872)74-02-29 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Ярославль (4852)69-52-93

Смоленск (4812)29-41-54

Сочи (862)225-72-31

казахстан (/1/2)/2/-13