

# Лебедки серии WINCH

## Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: [bfy@nt-rt.ru](mailto:bfy@nt-rt.ru) || сайт: <https://bystron.nt-rt.ru/>

## WINCH 4T FOR SMALL TRACTOR

LA/MAL/01



Steel rope winch is designed for pulling and approaching wood. Connection to the three-point hitch of the small tractor. The overall structure is welded and reinforced with thickened materials to form a unit resistant to bending, cracking and other damage.

Rope winding is controlled mechanically / manually. The rope is wound directly onto the cylinder of the machine. As a brake we have a ratchet - a latch. The rope is led by the top swivel pulley and the lower swivel pulley. The top pulley is mounted on the bearing, the lower pulley is lightly attached to the pin and the rope can be unhooked.

### Technical parameters

● Depth	0,7 m
● Width	1 m
● Height with net	2,2 m
● Height w/o net	1,5 m
● Weight	250
● Tractive force	4T
● Brake (ratchet)	100% efficiency
● Average winding speed	0,9m/s
● Standard rope	rope 10mm/60m - SEAL, strength 58,4kN
● Rope alternative (no included in the price)	rope 10mm/60m - rolled, strength 103kN
● Tractor power from	15HP
● Cardan RPM	540 RMP
● Hinge type	I - small tractor
● Bottom rotary pulley	Yes
● Trail hinge	Yes

## WINCH 4T

LA/TRA/01



Steel rope winch is designed for pulling and approaching wood. Connection to the three-point hitch of the small tractor. The overall structure is welded and reinforced with thickened materials to form a unit resistant to bending, cracking and other damage.

Rope winding is controlled mechanically / manually. The rope is wound directly onto the cylinder of the machine. As a brake we have a ratch - a latch. The rope is led by the top swivel pulley and the lower swivel pulley. The top pulley is mounted on the bearing, the lower pulley is lightly attached to the pin and the rope can be unhooked.

### Technical parameters

● Depth	0,7 m
● Width	1,5 m
● Height with net	2,2 m
● Weight	300
● Tractive force	4t.
● Brake (ratchet)	100% efficiency
● Average winding speed	0,9m/s
● Standard rope	rope 11,2mm/45m - SEAL, strength 70,7kN
● Rope alternative included in price	rope 10mm/60m -SEAL, strength 58,4kN
● Rope alternative (no included in the price)	rope 10mm/60m - rolled, strength 103kN
● Tractor power from	25HP
● Cardan RPM	540 RMP
● Hinge type	II - as specified by the customer
● Bottom rotary pulley	Yes
● Trail hinge	Yes

## WINCH 4T HYDRAULIC

LA/TRA/05



### Technical parameters

● Depth	0,7 m
● Width	1,5 m
● Height with net	2,2 m
● Weight	310
● Tractive force	4t.
● Brake (ratchet)	100% efficiency
● Average winding speed	0,9m/s
● Standard rope	rope 11,2mm/45m - SEAL, strength 70,7kN
● Rope alternative included in price	rope 10mm/60m -SEAL, strength 58,4kN
● Rope alternative (no included in the price)	rope 10mm/60m - rolled, strength 103kN
● Tractor power from	25HP
● Cardan RPM	540 RMP
● Hinge type	II - as specified by the customer
● Bottom rotary pulley	Yes
● Trail hinge	Yes
● Control	hydraulic

This is a very powerful machine with hydraulic control designed for pulling and approaching wood. Using a rope winch, we can quickly and easily make work in the forest more efficient and professional. The machine is designed as an additional device for a tractor driven via a cardan shaft.

Connection to the three-point hitch of the tractor is according to the customer's specifications. The rope winding is controlled by a hydraulic distributor on the side of the machine by the operator. The machine is connected to the tractor's hydraulic circuit. A ratchet - a latch, which is controlled mechanically, acts as a brake.

The rope is guided by the upper swivel pulley and the lower swivel pulley. The upper pulley is mounted on a bearing, while the lower pulley is loosely attached to a pin and the rope can be unhooked.

The overall structure is welded and reinforced with thick-walled materials, which creates a unit resistant to bending, cracking and other damage.

The rope is terminated with a rope end with a sliding yoke.

## WINCH 7,5T

LA/TRA/03



Professional rope winch is designed for pulling and approaching wood. Connection to the three-point hitch of the small tractor. The overall structure is welded and reinforced with thickened materials to form a unit resistant to bending, cracking and other damage.

The winding control is by hydr. switchboard placed directly on the machine. Brake: ratch - latch.

The rope is winded directly onto the cylinder of the machine. As a brake we have a ratch - a latch. The rope is leaded by the top swivel pulley and the lower swivel pulley. The top pulley is mounted on the bearing, the lower pulley is lightly attached to the pin and the rope can be unhooked.

### Technical parameters

● Depth	1 m
● Width	1,5 m
● Height with net	2 m
● Height without net	1,6 m
● Weight	560 kg
● Tractive force	7,5t.
● Brake (ratchet)	100% efficiency
● Average winding speed	0,6m/s
● Standard rope	12,5mm/60m - SEAL, strength 93,4kN
● Control	hydraulic swith
● Tractor power from	60HP
● Cardan RPM	540 RMP
● Hinge type	II - as specified by the customer
● Bottom rotary pulley	Yes
● Trail hinge	Yes

## WINCH 4T WITH WIRELESS REMOTE CONTROL

LA/TRA/02



Steel rope winch is designed for pulling and approaching wood. Connection to the three-point hitch of the small tractor. The overall structure is welded and reinforced with thickened materials to form a unit resistant to bending, cracking and other damage.

The rope winding is controlled remotely by a wireless transmitter with a reach of 60m. Two pneumatic cylinders are controlled, first controls the winch clutch (rope winding) and second cylinder the brake (ratchet).

The rope is wound directly onto the cylinder of the machine. As a brake we have a ratchet - a latch. The rope is led by the top swivel pulley and the lower swivel pulley. The top pulley is mounted on the bearing, the lower pulley is lightly attached to the pin and the rope can be unhooked.

### Technical parameters

● Depth	0,7 m
● Width	1,5 m
● Height with net	2,2 m
● Weight	310
● Tractive force	4t.
● Brake (ratchet)	100% efficiency
● Average winding speed	0,9m/s
● Standard rope	rope 11,2mm/45m - SEAL, strength 70,7kN
● Rope alternative included in price	rope 10mm/60m -SEAL, strength 58,4kN
● Rope alternative (no included in the price)	rope 10mm/60m - rolled, strength 103kN
● Remote control	Wireless transmitter
● Tractor power from	25HP
● Cardan RPM	540 RMP
● Hinge type	II - as specified by the customer
● Bottom rotary pulley	Yes

## WINCH 7,5T WITH WIRELESS REMOTE CONTROL

LA/TRA/04



### Technical parameters

● Depth	1 m
● Width	1,5 m
● Height with net	2 m
● Height without net	1,6 m
● Weight	560 kg
● Tractive force	7,5 t
● Brake (ratchet)	100% efficiency
● Average winding speed	0,6m/s
● Standard rope	rope 12,5mm/60m, strength 93,4kN
● Remote control:	Wireless transmitter
● Tractor power from	60HP
● Cardan RPM	540 RMP
● Hinge type	II - as specified by the customer
● Bottom rotary pulley	Ano
● Trail hinge	Ano

Steel rope winch is designed for pulling and approaching wood. Connection to the three-point hitch of the tractor. The overall structure is welded and reinforced with thickened materials to form a unit resistant to bending, cracking and other damage.

The rope winding is controlled remotely by a wireless transmitter with a reach of 60m. Two PNEUMATIC cylinders are controlled, first controls the winch clutch (rope winding) and second cylinder the brake (ratchet).

The rope is wound directly onto the cylinder of the machine. As a brake we have a ratch - a latch. The rope is led by the top swivel pulley and the lower swivel pulley. From the lower pulley the rope can be unhooked.

## По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

**Россия** +7(495)268-04-70

**Казахстан** +(727)345-47-04

**Беларусь** +(375)257-127-884

**Узбекистан** +998(71)205-18-59

**Киргизия** +996(312)96-26-47

эл.почта: [bfy@nt-rt.ru](mailto:bfy@nt-rt.ru) || сайт: <https://bystron.nt-rt.ru/>